

YOUR
SMART
ENERGY



SMILE5

RESIDENTIAL SERIES

POWER

5 / 4.6 kW inverter

CAPACITY

2.9 / 5.7 / 10.1 / 13.3 kWh
Battery Modular
expandable to 80.0 kWh



reddot design award 2018



product
design award 2018



5kW single phase hybrid inverter

Fast response

UPS ability

24/7 Monitoring

- S**elf sufficient
- M**odular battery
- I**ntelligent control
- L**ong lifespan
- E**ssential load protected
- 5** kW system



SMILE5



Model		SMILE5			
System Specification					
Nominal Output Power		5000 W			
Capacity Range	2.9 ~ 17.2 kWh (96% DoD)	5.7 ~ 34.4 kWh (96% DoD)	10.1 ~ 60.6 kWh (96% DoD)	13.3 ~ 80.0 kWh (100% DoD)	
Usable Capacity Range	2.8 ~ 16.5 kWh	5.5 ~ 33.0 kWh	9.7 ~ 58.1 kWh	13.3 ~ 80.0 kWh	
Battery Chemistry		LFP (LiFePO4)			
IP Protection		IP65			
Warranty		5 Year Product Warranty, 10 Year Battery Warranty			

Inverter Technical Specification			
Model	SMILE5-INV	Rated Frequency	50 / 60 Hz
Max. PV Input Power	7500 W	Phase	Single-Phase
Max. PV Input Current	15 A / 15 A	Backup	UPS
Max. PV Input Voltage	550 V	Display	LCD
MPPT Number	2	Communication	Ethernet / WIFI
MPPT Voltage Range	70 ~ 540 V	Start Up DC Voltage	125 V
Max. PV Short-circuit Current	18 A / 18 A	Relative Humidity	0 ~ 90% (No Condensing)
Max. Charging/Discharging Current	100 A	Dimension (W x D x H)	610 x 210 x 627 mm
Max. Charging/Discharging Power	5000 W	Weight	27.7 kg
Rated Voltage	230 V	EMC	EN 61000-6-1/2/3/4
Safety		IEC 62109	
Grid Regulation		AS4777.2	

Battery Technical Specification				
Module Model	M4856-P	SMILE5-BAT	SMILE-BAT-10.1P	SMILE-BAT-13.3P
Module Capacity	2.9 kWh	5.7 kWh	10.1 kWh	13.3 kWh
Module Nominal Voltage	51.2 V	51.2 V	48 V	48 V
Operating Temperature Range	-10 °C ~ 50 °C*	-10 °C ~ 50 °C*	-10 °C ~ 50 °C*	-10 °C ~ 50 °C*
Max. Modules in Parallel	6	6	6	6**
Max. Charging/Discharging Current	56 A	56 A	100 A	100A
Cycle Life	10 000***	10 000***	8000***	8000***

* When the ambient temperature is too low or too high, the performance of battery may be limited.

** ≥2 needs to install expansion pack

*** Under specific test conditions



Headquarter: Alpha ESS Co., Ltd.
 ☎ +86 513 8060 6891
 ✉ info@alpha-ess.com
 🌐 www.alpha-ess.com
 📍 Jiuhua Road 888, Nantong High-Tech Industrial Development Zone, Nantong City, 226300

Alpha ESS Suzhou Co., Ltd.
 ☎ +86 512 6828 7609
 ✉ info@alpha-ess.com
 🌐 www.alpha-ess.com
 📍 Building 10-A, Canal Town Industrial Park, 99 Taihu E Rd, Wuzhong District, Suzhou 215000

Australia: Alpha ESS Australia Pty. Ltd.
 ☎ +61 402 500 520 (Sales)
 +61 1300 968 933 (Technical Support)
 ✉ australia@alpha-ess.com
 🌐 www.alpha-ess.com.au
 📍 Unit 1, 2 Ralph Street Alexandria NSW 2015

Germany: Alpha ESS Europe GmbH
 ☎ +49 6103 4591 601
 ✉ europe@alpha-ess.de
 🌐 www.alpha-ess.de
 📍 Paul-Ehrlich-Straße 1a, D-63225 Langen, Hessen

Italy: Alpha ESS Italy S.r.l.
 ☎ +39 599 239 50
 ✉ info@alpha-ess.it
 🌐 www.alpha-ess.it
 📍 Via Loda, 17-41013 Castelfranco Emilia (MO)

Korea: Alpha ESS Korea Co., Ltd.
 ☎ +82 64 721 2004
 ✉ korea@alpha-ess.com
 📍 2F, 19-4, Nohyeong 11-gil, Jeju-si, Jeju-do, Republic of Korea

UK: Alpha ESS UK Ltd.
 ✉ uk@alpha-ess.com
 📍 Drake House, Long Street, Dursley, gl11 4hh